

EC type examination certificate
EG-Baumusterprüfbescheinigung

CE-0085BP5461

Product Identification No.
Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EC Gas Appliances Directive (2009/142/EC) <i>EG-Gasgeräterichtlinie (2009/142/EG)</i>
Owner of Certificate <i>Zertifikatinhaber</i>	SIT S.p.A. Viale dell'Industria, 31-33, I-35129 Padova
Distributor <i>Vertreiber</i>	SIT S.p.A. Viale dell'Industria, 31-33, I-35129 Padova
Product Category <i>Produktart</i>	accessories for gas appliances/pressure equipment: Burner control (4130)
Product Description <i>Produktbezeichnung</i>	Burner control for gas-burner with or without fan
Model <i>Modell</i>	BIC 0.580. ...
Countries of Destination <i>Bestimmungsländer</i>	European Union, CH, IS, NO, TR
Test Reports <i>Prüfberichte</i>	supplement test: GA 47 2017 Z7 from 28.02.2018 (TRG) supplement test: GA 47 2017 B8 from 28.02.2018 (TRG)
Test Basis <i>Prüfgrundlagen</i>	2009/142/EG (30.11.2009) DIN EN 298 (01.11.2012) DIN EN 298 (01.01.2004)

File Number 18-0263-GEA
Aktenzeichen

03.04.2018 Rie A-1/2 
Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of gas appliances under EC Directive

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Gasgeräten gemäß EG-Richtlinie 2009/142/EG.



DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Elektrical Data 230 V AC, 50 Hz, IP00
Elektrische Daten

Type Typ	Technical Data Technische Daten	Remarks Bemerkungen
...231	identification code: B/M/R/L/X/N safety time: 7 s ambient temperature range: -10...+60 °C	
...125; ...126; ...200	identification code: B/M/C/L/X/N safety time: 10 s ambient temperature range: -20...+60 °C	
...130; ...131; ...132; ...133; ...137; ...141; ...142; ...143; ...236; ...237	identification code: B/M/R/L/X/N safety time: 10 s ambient temperature range: 0...+60 °C	
...134; ...144; ...159; ...140; ...148; ...154	identification code: B/M/R/L/X/N safety time: 7 s ambient temperature range: -10...+60 °C	
...136	identification code: F/M/R/L/X/N safety time: 10 s ambient temperature range: 0...+60 °C	
...217; ...225; ...226; ...227; ...228; ...229	identification code: B/M/R/L/X/N safety time: 10 s ambient temperature range: -10...+60 °C	
...145	identification code: F/M/R/L/X/N safety time: 7 s ambient temperature range: -10...+60 °C	
...189; ...191; ...192	identification code: A/M/R/L/X/N safety time: 7 s ambient temperature range: 0...+60 °C	

Type Variation Ausführungsvariante	Explanations Erläuterungen
BIC 0.580.125	for fixed fan-speed
BIC 0.580.126; BIC 0.580.200	for modulating fan-speed
BIC 0.580.130; BIC 0.580.136	for gas-burner with fan
BIC 0.580.131; BIC 0.580.145	for atmospheric gas-burner
BIC 0.580.132; BIC 0.580.133; BIC 0.580.134	for gas-burner with or without fan
BIC 0.580.137; BIC 0.580.140; BIC 0.580.226	for gas-burner with or without fan
BIC 0.580.141; BIC 0.580.142; BIC 0.580.143	for gas-burner with or without fan
BIC 0.580.236; BIC 0.580.225; BIC 0.580.227	for gas-burner with or without fan
BIC 0.580.144; BIC 0.580.148; BIC 0.580.228	for gas-burner with or without fan
BIC 0.580.237; BIC 0.580.159; BIC 0.580.154	for gas-burner with or without fan
BIC 580.189; BIC 0.580.191; BIC 0.580.192	for gas-burner without fan
BIC 0.580.217; BIC 0.580.229; BIC 0.580.231	for gas-burner with or without fan