



Certificate of Compliance

Certificate: 1111412

Master Contract: 189456

Project: 80091754

Date Issued: 2021-07-23

Issued To: SIT SPA
Viale dell' Industria, 31-33
Padova, Padova, 35129
Italy

Attention: Giorgia Bozzolan

The products listed below are eligible to bear the CSA Mark shown with adjacent indicators 'C' and 'US' for Canada and US or with adjacent indicator 'US' for US only or without either indicator for Canada only.

Issued by: *Bob Greene*
Bob Greene



PRODUCTS

CLASS - C333507 - SYSTEMS (GAS) Oxygen Depletion Safety Shutoff

CLASS - C333587 - SYSTEMS (GAS) Oxygen Depletion Safety Shutoff-Certified to U.S. Standards

Model Number

For Use With Natural Gas

Oxygen Depletion Safety Shutoff Systems

Trade Name: OXYPROTECTOR

82(01,02,03,04,05,08,09,10,11,12,13,14,15,16,18,19,20,21,22,24,25,27,28,29,30,31,32,33,35,36,37,38,50,51,52,53,54) Pilot burner assembly and a S.I.T. 0.630 Control



Certificate: 1111412
Project: 80091754

Master Contract: 189456
Date Issued: 2021-07-23

For Use With Liquefied Petroleum Gases
Oxygen Depletion Safety Shutoff Systems

Trade Name: OXYPROTECTOR

84(01,02,03,04,05,08,09,10,11,12,13,14,16,17,18,20,21,22,23,24,26,27,28,29,30,31,32,33,34,37,39) Pilot burner assembly and a S.I.T. 0.630 Control

The 8200 and 8400 Series systems must be used with gas pressure regulator the design of which is certified by CSA for main burner and pilot load application. It must have a minimum regulation capacity and a maximum individual load capacity greater than the input rating of the appliance and an outlet pressure range of 3.5 to 10.5 in. w.c. for natural gas and 8.0 to 13.0 in. w.c. for liquefied petroleum gases. The model no. 8213 may have an outlet pressure range of 3.0 to 7.0 in. w.c. for natural gas. The model no. 8250 may have an outlet pressure of 1.5 in. to 4.0 in. w.c. for natural gas. The models 82(51,52,53,54) may have an outlet pressure of 2.0 in. to 10.5 in. w.c. for natural gas.

APPLICABLE REQUIREMENTS

ANSI Z21.20-2005 (R2016)
ANSI Z21.20a-2008 (R2016)

Automatic Gas Ignition Systems and Components
Addenda